

# CITYMAXX

- Hydraulic wings
- Hydraulic angle
- Subframe



# CITYMAXX

Snow plow with hydraulic wings and angle.

The CityMaxx is installed in front of a tractor with a Universal Subframe exclusive to Metal Pless or on a front 3 point hitch.

TECHNICAL SHEET



SCAN ME  
with your camera application on any phone

# CITYMAXX



## Available in HD or LE

Includes angular system and tractor subframe or 3 point hitch.

This system requires 3 or 4 sets of oil outlets.

Not included: hydraulic hoses and connectors from the blade to the tractor.

MODEL	BLADE DIMENSIONS			APPLICATION	APPROX. WEIGHT
	BOX	HEIGHT	EXTENDED		
CT 1048-18 <small>HD or LE</small>	10'	48"	18'	150 HP and up	3 100 lbs
* CT 1048-20 <small>HD or LE</small>	10'	48"	20'	150 HP and up	3 350 lbs
CT 1248-20 <small>HD or LE</small>	12'	48"	20'	150 HP and up	3 400 lbs
* CT 1248-22 <small>HD or LE</small>	12'	48"	22'	150 HP and up	3 630 lbs

\* Available only for tractors with a 3 point hitch in front.

Prices, specs, models and/or model numbers are subject to change.


## OPTIONS (not included)

- "High Speed" (accentuated curve of the mouldboard) **[HS]**.
- 3 point hitch attachment **[A3P, A3P6F or A3P6B]**.
- Carbide cutting edge **[CCE]**.
- Electric hydraulic diverter valve 3 or 4 sets of oil outlets 12 volts **[DVDE3 or DVDE4]** 13 or 24 GPM to be specified.
- Non standard color **[NSC1]**.
- Nitrogen accumulator package installed on the lift cylinder **[AAC]**.
- Electric valve and joystick **[JSC3 or JSC4]**: electric over hydraulic 3 or 4 spools mounted on blade with electric control and necessary cable for the installation in the tractor cab.

ALSO AVAILABLE



BLADE POSITIONS



The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.