

EXTENDMAXX

- Extendable plow
- Hydraulic wings
- Hydraulic angle
- Subframe



EXTENDMAXX

Extendable snow plow blade with hydraulic wings and angle.

The ExtendMaxx is installed in front of a tractor with a Universal Subframe exclusive to Metal Pless.

TECHNICAL SHEET



SCAN ME with your camera application on any phone

EXTENDMAXX



HD
SOFT DRIVE TRIP EDGE



Available in HD or LE

Includes angular system and subframe.

This system requires 5 sets of oil outlets.

Not included: hydraulic hoses and connectors from the blade to the tractor.

MODEL	BLADE DIMENSIONS			EXTENDED EXTENSION ONLY	APPLICATION	APPROX. WEIGHT
	BOX	HEIGHT	FULLY EXTENDED			
EXT 0736-17 <small>HD or LE</small>	7'	36"	17'	11'	125 HP and up	2 500 lbs
EXT 0836-19 <small>HD or LE</small>	8'	36"	19'	13'	125 HP and up	2 866 lbs
EXT 1036-21 <small>HD or LE</small>	10'	36"	21'	15'	125 HP and up	3 075 lbs

Prices, specs, models and/or model numbers are subject to change.

ALSO AVAILABLE




LE
LIVE EDGE

OPTIONS (not included)

- Tire saver **(PP)**.
- 3 point hitch attachment **(A3P)**.
- Carbide cutting edge **(CCE)**.
- Non standard colour **(NSC1)**.
- Electric hydraulic diverter valve 5 sets of oil outlets **(DVDES)** 13 or 24 GPM to be specified.
- Nitrogen accumulator package installed on the lift cylinder **(AAC)**.
- Electric valve and joystick **(JSC5)**: electric over hydraulic 5 spools mounted on blade with electric control and necessary cable for the installation in the tractor cab..

BLADE POSITIONS



The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.