

PLOWMAXX

- Hydraulic wings
- Hydraulic angle



PLOWMAXX

Snow plow with hydraulic wings and angle.

The PlowMaxx can be installed on a skid steer, backhoe or wheel loader.

TECHNICAL SHEET



SCAN ME
with your camera application on any phone

PLOWMAXX



LE
LIVE EDGE



STD
STANDARD

Available in STD, HD or LE

This system requires 1 set of oil outlets.

- Not included: - hydraulic hoses from the blade to the vehicle.
- quick coupler


ALSO AVAILABLE



HD

SOFT DRIVE TRIP EDGE

BLADE POSITIONS



MODEL	BLADE DIMENSIONS			APPLICATION	APPROX. WEIGHT
	BOX	HEIGHT	EXTENDED		
PLLT 04.527-8.5	STD 4'6"	27"	8'6"	6 000 lbs max.	875 lbs
PLLT 0527-10	STD 5'	27"	10'	6 000 lbs max.	1 114 lbs
PLLT 0627-11	STD 6'	27"	11'	6 000 lbs max.	1 242 lbs
PLLT 0727-12	STD 7'	27"	12'	6 000 lbs max.	1 297 lbs
PLSS 0630-11	STD or LE 6'	30"	11'	12 000 lbs max.	1 640 lbs
PLSS 0730-12	STD or HD 7'	30"	12'	12 000 lbs max.	1 740 lbs
PLSS 0830-13	STD, HD or LE 8'	30"	13'	12 000 lbs max.	1 930 lbs

PLBH 0736-13	HD or LE 7'	36"	13'	18 000 lbs max.	2 107 lbs
PLBH 0836-14	STD, HD or LE 8'	36"	14'	18 000 lbs max.	2 250 lbs
PLBH 0936-15	STD, HD or LE 9'	36"	15'	20 000 lbs max.	2 340 lbs
PLBH 0836-16	HD or LE 8'	36"	16'	20 000 lbs max.	2 435 lbs
PLBH 1036-16	STD, HD or LE 10'	36"	16'	20 000 lbs max.	2 427 lbs
PLBH 1236-18	STD, HD or LE 12'	36"	18'	20 000 lbs max.	2 620 lbs

PLLD 0842-15	HD or LE 8'	42"	15'	25 000 lbs max.	2 842 lbs
PLLD 0842-16	HD or LE 8'	42"	16'	25 000 lbs max.	3 000 lbs
PLLD 1042-17	HD or LE 10'	42"	17'	25 000 lbs max.	3 205 lbs
PLLD 1042-18	HD or LE 10'	42"	18'	25 000 lbs max.	3 277 lbs
PLLD 1242-19	STD, HD or LE 12'	42"	19'	25 000 lbs max.	3 326 lbs

OPTIONS (not included)

- Quick coupler.
- Electric hydraulic diverter valve 3 sets of oil outlets 12 or 24 volts (DVDE3) 24 GPM maximum capacity, Bobcat 7 pins.
- Carbide cutting edge (CCE).
- Curb runners (CR36-STD).
- Non standard colour (NSC1).
- Teflon cutting edge 3/4" x 6" (TCE3/4).
- Electric valve and joystick (JSC3)
12 or 24 volts: electric over hydraulic 3 spools mounted on blade with electric control and necessary cable for the installation in the tractor cab..

Prices, specs, models and/or model numbers are subject to change.

The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.