

SIDEMAXX

- Sidewalk blade
- Hydraulic angle



TECHNICAL SHEET



SCAN ME with your camera application on any phone

SIDEMAXXX

This system requires 2 sets of oil outlets.
 Not included: hydraulic hoses and connectors from the blade to the vehicle.

MODEL	BLADE DIMENSIONS		APPLICATION	APPROX. WEIGHT
	WIDTH	HEIGHT		
SM 527/60 STD	60"	27"	35 HP and up	550 lbs
SM 530/60LE LE	60"	30"	35 HP and up	725 lbs

Prices, specs, models and/or model numbers are subject to change.

OPTIONS (not included)

- Carbide cutting edge (CCE).
- Joystick and valve (DVDE2).
- Non standard colour (NSC1).

Available in:

- 3 point hitch (category 2)
- With trackless coupler
- With tractor subframe

Option #1: Heavy duty 18" hydraulic extension.

Option #2: Tilt 12" hydraulic pivot from up/down (requires hydraulic float).

Option #3: 14" hydraulic sideshift (5" to the left and 9" to the right).

Possible options configuration: 1 & 2 / 2 & 3 / 1, 2 & 3.

An additional set of oil outlets are needed per option.

SIDEMAXX-X

- Sidewalk blade
- Hydraulic angle



TECHNICAL SHEET



SCAN ME with your camera application on any phone

SIDEMAXXX-X

This system requires 3 sets of oil outlets.
 Not included: hydraulic hoses and connectors from the blade to the vehicle.

MODEL	BLADE DIMENSIONS			APPLICATION	APPROX. WEIGHT
	STRAIGHT	FRONT & REAR "V"	HEIGHT		
SDX 532 STD	60"	48"	32"	35 HP and up	550 lbs

Prices, specs, models and/or model numbers are subject to change.


OPTIONS (not included)

- Carbide cutting edge (CCE).
- Non standard color (NSC1).
- Electric hydraulic diverter valve 3 sets of oil outlets 12 volts (DVDE3) 13 or 24 GPM to be specified.

Available in:

- 3 point hitch (category 1&2)
- With trackless coupler
- With tractor subframe

BLADE POSITIONS



The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.