

WINGMAXX

- Front blade with side wing
- Hydraulic angle



WINGMAXX

Snow plow with hydraulic angle and side wing.

The WingMaxx is installed on a wheel loader or on a tractor with a Universal Subframe exclusive to Metal Pless.

WINGMAXX



SCAN ME
with your camera
application
on any phone

WINGMAXX

HS*Optional

High Speed, accentuated curve of the mouldboard.

HD

SOFT DRIVE TRIP EDGE



LE

LIVE EDGE

Available in HD or LE

Loader: includes quick coupler and DVDE3, 24 volts, 24 GPM.

Tractor: includes subframe only

Includes front blade and side wing.

This system requires 1 or 4 sets of oil outlets.

Not included: hydraulic hoses and connectors from the blade to the vehicle.

MODEL	FRONT BLADE		SIDE WING		APPLICATION	APPROX. WEIGHT
	WIDTH	HEIGHT	WIDTH	HEIGHT		
WING 12-08	HD or LE	12'	42"	8'	36"	150 HP and up 3 600 lbs
WING 12-09	HD or LE	12'	42"	9'	36"	150 HP and up 3 750 lbs
WING 12-10	VHD or LE	12'	42"	10'	36"	150 HP and up 3 900 lbs

Prices, specs, models and/or model numbers are subject to change.

OPTIONS (not included)

- "High Speed" (Accentuated curve of the mouldboard) **(HS)**.
- Carbide cutting edge **(CCE)**.
- Non standard color **(NSC1)**.
- Nitrogen accumulator package installed on the lift cylinder **(AAC)**.
- Electric valve and joystick **(JSC4)**: electric over hydraulic 4 spools mounted on the blade with electric control and necessary cable for the installation in the cab.

The width of the blade does not determine the real dimension of the product. Pictures shown might have some options.